



Lexmark MX331adn

Get output up to 40 pages per minute*, plus single-side automatic scanning, copying, faxing and touch-screen convenience, all in the compact Lexmark MX331adn.

Part Number

29S0150

Print Technology

Monochrome Laser

Function

Color Scanning, Copying, Faxing, Network Scanning, Printing

Workgroup Size

Small Workgroup

Touch Screen Display

Yes

Display

2.8 inch (7.2 cm) LCD touch panel

Print Speed (Letter, Black)

Up to 40 ppm⁶

Print Speed (Letter, Black) Duplex

Up to 17 spm⁶

Time to First Page (Black)

As fast as 6.2 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

2400 IQ (2400 x 600 dpi), 600 x 600 dpi

Copy Speed (Letter, Black)

Up to 40 cpm⁶

Copy Speed (Letter, Black) Duplex

Up to 17 spm⁶

Time to First Copy (Black)

As fast as 6.2 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 46 / 48 sides per minute

A4/Ltr Simplex Scan Speed (Color)

Up to 20 / 21 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Up to N/A sides per minute

A4/Ltr Duplex Scan Speed (Color)

Up to N/A sides per minute

Scan Area, Maximum

8.5 x 14 inches

ADF Scan

Simplex

Scanner Type

Flatbed scanner with ADF

Scan Technology

CIS

Optical Scanning Resolution

up to 600 X 600 ppi (color)

Scan File Formats (Send as)

JPEG, JPG, PDF, TIFF

Scan Destinations

e-mail, FTP, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

ITU T.30, V.34 Half-Duplex, 33.6 Kbps

Fax Transmission Speed

< 3 seconds per page

Processor Speed

Dual Core, 1.0 GHz

Memory, Standard

512 MB

Memory, Maximum

512 MB

Hard Disk

Not Available

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5, Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame Presentation Server 4.0

Linux Operating Systems Supported

openSUSE Linux 42.3, Fedora 27, 28, 29, Ubuntu 16.04, 18.04 LTS, Red Hat Enterprise Linux WS 6.10, 7.5, 7.6, Debian 9.4, 9.5, 9.6, Debian GNU/Linux 8.11, openSUSE Linux 15, SUSE Linux Enterprise Server 12 SP3, SUSE Linux Enterprise Server 12 SP4, SUSE Linux Enterprise Server 15

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Included Paper Handling

250-Sheet Input, 100-Sheet Multipurpose Feeder, 150-Sheet Output Bin, Integrated Duplex

Optional Paper Handling

550-Sheet Tray

Paper Input Capacity, Standard

Up to 350 pages 20 lb or 75 gsm bond

Paper Input Capacity, Maximum

Up to 900 pages 20 lb or 75 gsm bond

Paper Output Capacity, Standard

Up to 150 pages 20 lb or 75 gsm bond

Paper Output Capacity, Maximum

Up to 150 pages 20 lb or 75 gsm bond

Paper Weight Range Supported - Standard Tray (lb.)

16 - 32 lb.

Paper Weight Range Supported - Multipurpose Feeder (lb.)

16 - 58 lb.

ADF

50-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 50 pages 20 lb or 75 gsm bond

ADF Paper Output Capacity

Up to 50 pages 20 lb or 75 gsm bond

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

3

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Standard Ports

Ethernet 10/100BaseTX (RJ-45), USB Compatible with USB 2.0 Specification (Type B)

Direct USB

Yes

Ethernet Network

Yes

Wireless

Wireless Option

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP, IPSEC w/ IPv4, IPSEC w/ IPv6, ICMP, IGMP, 802.1x

Network Printing Methods

LPR/LPD, Enhanced IP (Port 9400), FTP, TFTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, DHCP, ICMP, DNS, SMTP, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS

Printable Area

0.2 inches of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 5e Emulation, PCL 6 Emulation, PostScript 3 Emulation, Direct Image, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, 89 scalable PostScript fonts, For more information, refer to the Technical Reference., 89 scalable PCL fonts

Laser Cartridge Yields (up to)⁵

3,000-page Cartridge, 15,000-page High Yield Cartridge,

Imaging Unit Estimated Yield

Up to 40000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

1,500-page Return Program Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (in. - H x W x D)

15.16 x 16.54 x 18.31 in.

Packaged Weight (lb.)

32.41 lb.

Size (in. - H x W x D)

13.3 x 16.2 x 14.4 in.

Weight (lb.)

28.2 lb.

Noise Level, Idle

14 dBA

Noise Level (Print), Operating

53 dBA

Duplex Print Noise Level, Operating

50 dBA

Noise Level (Copy), Operating

54 dBA

Noise Level (Scan), Operating

55 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.1 watts

Average Power (Sleep Mode)

0.8 watts

Average Power (Ready Mode)

watts

Average Power (Printing)

530 watts

Average Power (Copying)

watts

Average Power (Scanning)

watts

ENERGY STAR Typical Electricity Consumption (TEC)

0.44 kilowatt-hours per week

Limited Warranty - See Statement of Limited Warranty

1-Year Advanced Exchange, Next Business Day

Product Certifications

ENERGY STAR, ICES-003 Class B, BSMI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECF, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, DE-UZ 205, China Green Product (CGP)

Maximum Monthly Duty Cycle

Up to 50000 pages per month³

Recommended Monthly Page Volume

500 - 5000 pages²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Meters (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

Harmonized Tariff Code

8443.31.0000

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average standard page yield value declared in accordance with ISO/IEC 19752.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



Callout	Availability	Description
1	Standard	2.8 inch (7.2 cm) LCD touch panel
2	Standard	100-Sheet Multipurpose Feeder
3	Standard	250-Sheet Input
4	Optional	550-Sheet Tray

P/N Toner Cartridges

55B0HA0	Lexmark 55B0HA0 High Yield Toner Cartridge
55B1000	Lexmark 55B1000 Return Program Toner Cartridge
55B1H00	Lexmark 55B1H00 High Yield Return Program Toner Cartridge
55B0ZA0	Lexmark 55B0ZA0 Photoconductor Unit
55B100E	Lexmark 55B100E Contract Toner Cartridge
55B1H0E	Lexmark 55B1H0E High Yield Contract Toner Cartridge

P/N Paper Handling

29S0600	550-Sheet Tray
---------	----------------

P/N Furniture

3073173	Swivel Cabinet
35S8502	Adjustable Printer Stand

P/N Connectivity

27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
1021294	USB Cable (2-meter)

P/N Extended Warranties

2371970	MX331 2-Years Total (1+1) Exchange Service
2371971	MX331 3-Years Total (1+2) Exchange Service
2371972	MX331 4-Years Total (1+3) Exchange Service
2371973	MX331 5-Years Total (1+4) Exchange Service
2371974	MX331 6-Years Total (1+5) Exchange Service
2371975	MX331 7-Years Total (1+6) Exchange Service
2371976	MX331 1-Year Exchange Service Renewal
2371977	MX331 2-Year Exchange Service Renewal
2371978	MX331 3-Year Exchange Service Renewal
2371979	MX331 4-Year Exchange Service Renewal
2371980	MX331 Per Call 1 Time NBD Exchange Extended Warranty
2371981	MX331 1-Year Post Wty NBD Exchange Extended Warranty
2371984	MX331 Upgrade to Onsite Service
2371985	MX331 2-Years Total (1+1) Onsite Service
2371986	MX331 3-Years Total (1+2) Onsite Service
2371987	MX331 4-Years Total (1+3) Onsite Service
2371988	MX331 5-Years Total (1+4) Onsite Service
2371989	MX331 6-Years Total (1+5) Onsite Service
2371990	MX331 7-Years Total (1+6) Onsite Service
2371991	MX331 1-Year Onsite Service Renewal
2371992	MX331 2-Year Onsite Service Renewal
2371993	MX331 3-Year Onsite Service Renewal
2371994	MX331 4-Year Onsite Service Renewal
2371995	MX331 Per Call OSR 1 Time NBD Extended Warranty

P/N Extended Warranties

2371996	MX331 1-Year Post Wty OSR NBD Ext Warranty
2372009	MX331 1-Year Lite Onsite Service
2372010	MX331 2-Year Lite Onsite Service
2372011	MX331 3-Year Lite Onsite Service
2372012	MX331 4-Year Lite Onsite Service
2372013	MX331 5-Year Lite Onsite Service
2372014	MX331 6-Year Lite Onsite Service
2372015	MX331 1-Year Lite Onsite Service Renewal
2372016	MX331 2-Year Lite Onsite Service Renewal
2372017	MX331 3-Year Lite Onsite Service Renewal
2372018	MX331 4-Year Lite Onsite Service Renewal